Multicrete Power Pack – 35, 68 & 74HP

Technical Data Sheet

Power Pack Technical Specifications

	35 HP	68 HP	74 HP
Dimensions (Length, Width, Height)	61 ½ / 56 ½ / 61	60 ½ / 60 ⅜ / 64 ½	56 ½ 56 ½
Diesel Tank	40 USG Diesel Tank	40 USG Diesel Tank	40 USG Diesel Tank
Hydraulic Tank	50 USG Hydraulic Tank	70 USG Hydraulic Tank	72 USG Hydraulic Tank
Maximum Pressure	1,800 PSI	3,770 PSI	2,000 PSI
Hydraulic Flow	33 GPM	35 GPM	44 GPM
Weight	3,070 lbs.	Approx. 2,800-3,000 lbs.	2,903 lbs.

Power Pack Procedure

Multicrete Power Packs can work standalone or in conjunction with other Multicrete Grout units. Before operating the Power Pack or grout machinery, the operator must:

1. Examine engine oil levels
2. Examine hydraulic oil levels
3. Examine antifreeze levels
4. Inspect hydraulic couplers for damage, corrosion or wear and making sure the coupler is clear of debris before connecting
5. Turn the Master Switch to the **“ON”** function
6. Turn the Power Switch on the control panel
7. Press the **“START”** button and begin operation